



### [features]

- No Daily Calibration Required
- Auto Discrimination of Symbologies
- LEDs Display ANSI Grade & Bar Tolerance
- Center Scan Key
- N.I.S.T. Traceable
- Element Detail Analysis
- ANSI & Traditional Grading
- One touch "Hot" keys for Help, Print, and UPC Mag
- Custom Program Options Available
- Corrugated Option - adjusts Symbol Contrast per Fibre Box Association guidelines



### Stratix Combines Ease-of-Use & Pinpoint Accuracy

Making sure your bar codes are scannable is a crucial part of today's business. Avoid mistakes, damaged customer relationships, or even costly fines. Stratix makes verification easier and more accurate than ever before, with the new Xaminer Elite series bar code verifiers. Whether you must verify one-dimensional or two-dimensional (PDF-417 & GS1 DataBar) symbologies, there's an Xaminer Elite model that's right for your business — and your budget!

### Bar Code Verification in a Simple Integrated Unit

The Xaminer, Elite IS, Elite IS Plus & Elite IS Point & Shoot bar code verifiers from Stratix give you the industry's highest quality bar code verification for either one-dimensional or two-dimensional (GS1 DataBar and PDF - 417) bar codes — all in a single unit. The Xaminer Elite verifiers come standard with a fully integrated laser scanner. No more cables to snag or cords to tangle. For additional flexibility and industry-specific applications, the Xaminer Elite IS and Elite IS Plus can have a 6, 10, or 20 mil wand can added. The Xaminer Elite Wand is ideal when you need quality verification equipment at the best price.

### Maximize Your Investment

As your verification needs change, so can your Xaminer Elite verifier. All Xaminer Elite verifiers come equipped with expandable firmware allowing for wand or integrated scan engine upgrades in the future. As your needs for bar code symbologies change, so can your Xaminer Elite verifier with a simple software and/or hardware upgrade from the Stratix Service Department. The Xaminer Elite is a verifier that will truly meet all of your verification needs today and tomorrow.

### Calibration Check Routine

Need to make sure your verifier investment is operating properly? Only Stratix Elite IS and Elite IS Plus verifiers ship with a calibration check routine that will allow an operator to check calibration in under 30 seconds, right at your worksite!

# Specifications



## Xaminer Elite Verifier Models

- 9015 Xaminer Elite IS Point & Shoot (integrated laser)**  
Partial ANSI  
Includes: 4 AA Batteries, User's Manual and Training Video CD
- 9020 Xaminer Elite IS (integrated laser)**  
Dual ANSI - Full ANSI and Partial ANSI Grading  
Includes: AC Adapter, PC Communications Cable, UPC-A Calibration Check Card, Table Top Stand, User's Manual and Training Video CD
- 9030 Xaminer Elite IS Plus (integrated laser)**  
Dual ANSI - Full ANSI and Partial ANSI Grading  
Includes: AC Adapter, PC Communications Cable, UPC-A Calibration Check Card, Table Top Stand and User's Manual and Training Video CD

## Symbologies Verified

### Elite IS & Elite IS Point & Shoot:

- UPC-A Addendum 2,5 (GTIN 12)
- UPC-E Addendum 2,5 (GTIN 12)
- EAN-8 (GTIN 8)
- EAN-13 Addendum 2,5 (GTIN 13)
- Code 128
  - Standard AIM
  - UCC/EAN SCC-14 (GTIN 14), SSCC-18
- Coupon Code (UPC-A with GS1 128 coupon extended code)
- Code 39
- Interleaved 2 of 5 (ITF)
  - Case Code SCC-14 (GTIN 14)
- Code 93
- Codabar
- Pharma Code

### Elite IS Plus:

All symbologies plus: PDF-417 Standard, GS1 DataBar Family (Limited, Stacked, Truncated, Stacked Omni-Directional, Omni-Directional, Expanded, & Expanded Stacked), Composite Symbology (CC-A, CC-B, & CC-C), and Coupon Code (UPC-A with GS1 DataBar Expanded and GS1 DataBar Expanded only)

## 1D Laser Scanner (Elite IS, IS Point & Shoot, & IS Plus)

- Light Source: 650nm visible laser diode
- Scan Angle: 40° ± 2°
- Scan Patterns: Linear
- Minimum Print contrast: 20% absolute dark/light reflectance

## Performance Characteristics

- CPU: Motorola Coldfire
- Operating System: Proprietary
- Memory: 8MB (250 Scans)
- Interface/Communications: Serial RS232

## Physical Characteristics

- Dimensions: 3.25 in.D x 3.75in. H 82.55mm D x 95.25mm W x 203.2mm H
- Weight: 14oz (400grams)
- Display: LCD, 128 x 64 (8 rows x 20 columns)
- Power: 4 AA batteries or AC 110v Power Supply
- Notification: LEDs for ANSI grade & Bar Tolerance
- Keypad: 22 Key Numeric

## Wand Specs

- Light Source: 660nm
- Visible Red Light
- 6,10, and 20 mil apertures

## Environmental

- Operating Temperature: 14°-122° F
- Storage Temperature: -40°-158° F
- Relative Humidity: 0% to 85% relative humidity, non-condensing
- Sealing Specification: IP42

## Software

- |  |        |      |
|--|--------|------|
| Stratix Verification Software (SVS)<br>(single user license) | Part # | 7309 |
|--|--------|------|

## Accessories

### Wands:

- |        |       |    |
|--------|-------|----|
| 6 mil  | Part# | 6  |
| 10 mil | Part# | 10 |
| 20 mil | Part# | 20 |

### Printers:

- |                |       |           |
|----------------|-------|-----------|
| Dot Matrix     | Part# | 6613      |
| Direct Thermal | Part# | STXTECDTP |

### Paper/Ribbon:

- |                                      |        |      |
|--------------------------------------|--------|------|
| One-Ply Dot Matrix Printer Paper     | Part # | 6715 |
| Two-Ply Dot Matrix Printer Paper     | Part # | 6716 |
| Dot Matrix Printer Ribbon            | Part # | 6714 |
| One-Ply Direct Thermal Printer Paper | Part # | 6708 |

### Cases:

- |                       |        |          |
|-----------------------|--------|----------|
| Protective Carry Case | Part # | V6158BCS |
| Shoulder Harness      | Part # | 10038    |
| Belt Holster          | Part # | 10039    |

### Stands:

- |                 |        |       |
|-----------------|--------|-------|
| Table Top Stand | Part # | 10046 |
|-----------------|--------|-------|

### Power:


- |   |        |       |
|---|--------|-------|
| AC Adapter  | Part # | 10022 |
| PC Upload/Communcation Cable  | Part # | 1313  |
| Secondary Power Cable (110 volt)  | Part # | 1316  |
| AA Ni-MH Batteries  | Part # | 10026 |
| Battery Charger with 4 AA Ni-MH batteries<br>(110 volt and slow charging) | Part # | 10034 |
| Battery Charger<br>(no batteries included, 110 volt, and fast charging)   | Part # | 10033 |

## Regulatory

- Safety: UL E236508
- Emissions (EMI): FCC Part 15 Subpart B, Class A
- Laser Safety: CDRH 21

## Warranty

- 1 year manufacturer's defects warranty (parts & labor)



**Symbology, Incorporated**

800.328.2612, 763.315.8080  
[clientservices@symbology.com](mailto:clientservices@symbology.com)  
[www.symbology.com](http://www.symbology.com)